



3 1/2" NON-VACUUM DYNORBITAL-SPIRIT™ RANDOM ORBITAL SANDERS

- Replaceable drop-in motor
- Palm-style grip; colour coded composite lever (identifies orbit size)
- Low sound levels
- One-piece speed control dial
- Custom engineered composite cylinder; double row balancer bearing keeps out contaminants
- Includes low profile, premium urethane, weight-mated, non-vac pad
- Can be converted easily to self-generated or central vac model for hook-up to dust collection system

Model No.	TGY858
Mfg. No.	59015
Abrasive Information:	3 1/2" (89 mm) dia. discs
Pad Information:	3 1/2" (89 mm) dia. pad
Air Flow Rate @ 90 PSI:	16 SCFM
Sound Level:	73 dB (A)
Horsepower:	0.25 HP
Free Speed:	12 000 RPM
Air Pressure:	90 PSI
Air Inlet Thread:	1/4 NPT
Hose Size (I.D.):	1/4" (6 mm)
Orbit Diameter:	3/16" (4.8 mm)
Tool Spindle Thread:	5/16"- 24 female
Length:	6" (152 mm)
Height:	3 1/2" (89 mm)
Weight:	1.4 lbs. (0.64 kg)
Price/Each:	\$



3 1/2" NON-VACUUM DYNORBITAL® SUPREME RANDOM ORBITAL SANDERS

- Includes low profile, premium urethane, weight-mated, non-vac pad for use with PSA discs
- Can be converted easily to self-generated vac model for hook-up to dust collection system
- Random circular & elliptical motion produces superior finishes

Model No	TGY810
Mfg. No.	56800
Abrasive Information:	3 1/2" (89 mm) dia. discs
Pad Information:	3 1/2" (89 mm) dia.
Length:	6" 152 mm
Height:	3 3/4" (95 mm)
Weight:	2.1 lbs. (0.95 kg)
Air Flow Rate @ 90 PSI:	18 SCFM
Sound Level:	76 dB(A)
Horsepower:	0.24 HP
Free Speed:	12 000 RPM
Air Pressure:	90 PSI
Air Inlet Thread:	1/4 NPT
Hose Size (I.D.):	1/4" (6 mm)
Orbit Diameter:	3/16" (4.8 mm)
Tool Spindle Thread:	5/16"- 24 female
Price/ Each:	\$



5" & 6" NON-VACUUM DYNORBITAL® SUPREME RANDOM ORBITAL SANDERS

- Can be converted easily to self-generated vac model for hook-up to dust collection system
- Random circular & elliptical motion produces superior finishes
- Includes low profile, premium urethane, weight-mated, non-vac pad

Model No.	TGY813	TGY816
Mfg. No.	56815	56826
Abrasive Information:	5" (127 mm) dia. discs	6" (152 mm) dia. discs
Pad Information:	5" (127 mm) dia.	6" (152 mm) dia.
Air Flow Rate @ 90 PSI:	18 SCFM	18 SCFM
Sound Level:	79 dB (A)	79 dB (A)
Horsepower:	0.28 HP	0.24 HP
Free Speed:	12 000 RPM	12 000 RPM
Air Pressure:	90 PSI	90 PSI
Air Inlet Thread:	1/4 NPT	1/4 NPT
Hose Size (I.D.):	1/4" (6 mm)	1/4" (6 mm)
Orbit Diameter:	3/16" (4.8 mm)	3/16" (4.8 mm)
Tool Spindle Thread:	5/16"- 24 female	5/16"- 24 female
Length:	6 1/2" (165 mm)	7" (178 mm)
Height:	3 5/8" (92 mm)	3 1/2" (89 mm)
Weight:	2.1 lbs. (0.95 kg)	2.2 lbs. (1 kg)
Price/Each	\$	\$



AIR LINE CONNECTORS


- Swivels 360° at two pivot points allowing the air hose to drop directly to the floor while providing superb tool handling



THZ359



THZ360



THZ361



COMPOSITE DYNASWIVEL AIR LINE CONNECTORS

Model No.	THZ359
Mfg. No.	94300
Thread Size:	1/4" NPT
Weight:	2.15 oz. (0.06 kg)
Air Flow Range:	Up to 33 SCFM
Maximum Air Pressure:	150 PSI
Price/Each:	\$

1/4" NPT HEAVY-DUTY DYNASWIVEL AIR LINE CONNECTORS

Model No.	THZ361
Mfg. No.	95460
Air Inlet Thread Size:	1/4" NPT
Air Flow Range:	Up to 25 SCFM
Maximum Air Pressure:	150 PSI
Weight:	0.20 lbs. (0.09 kg)
Price/ Each:	\$

COMPOSITE FLOW CONTROL DYNASWIVEL AIR LINE CONNECTORS

Model No	THZ360
Mfg. No.	94407
Thread Size:	1/4" NPT
Air Flow Range:	Up to 46 SCFM
Maximum Air Pressure:	150 PSI
Weight:	2.4 oz. (0.08 kg)
Price/Each:	\$