



## ELECTRARAY® ROTATING WARNING LIGHTS

- A compact, economical rotating warning light designed for industrial use
- Innovative dome design features a single retaining screw that allows quick and easy access for inspection and relamping
- UL and cUL Listed for indoor/outdoor use
- Type 4X, IP66 enclosure
- Design makes it easily adaptable for a multitude of applications and provides an effective means of supplementing audible signaling devices
- Available in 120 VAC
- Integrated 1/2" pipe mount



Model No.	Mfg. No.	Colour	Price/Each
XC115	225-120A	Amber	
XC116	225-120R	Red	
XC281	225-120B	Blue	
XC282	225-120C	Clear	
XC283	225-120G	Green	

## VITALITE® ROTATING WARNING LIGHTS

- A compact, rotating light designed for in-plant applications
- Features a parabolic reflector that rotates around an incandescent lamp, providing 60 flashes per minute in all directions
- Available in 120 VAC
- Pipe and surface mount
- Type 4X, IP66 enclosure
- UL, cUL Listed and CSA certified



Model No.	Mfg. No.	Colour	Price/Each
XC112	1215-120A	Amber	
XC113	1215-120B	Blue	
XC114	1215-120R	Red	
XC273	1215-120C	Clear	
XC274	1215-1210G	Green	

## ELECTRAFLASH® STROBE WARNING LIGHTS

- Economical strobe light designed for a variety of industrial uses
- Compact warning light is less than 6" tall and 6" diameter
- 24 VDC or 120 VAC
- 4000-hour strobe tube
- Type 3R enclosure
- UL Listed and CSA certified



Model No.	Mfg. No.	Description	Price/Each
XC121	1415T-024A	24 VDC, Amber	
XC122	1415T-024R	24 VDC, Red	
XC284	1415T-024B	24 VDC, Blue	
XC123	1415T-120A	120 VAC, Amber	
XC124	1415T-120R	120 VAC, Red	
XC285	1415T-120B	120 VAC, Blue	

Note: Clear and green available upon request

## STREAMLINE® MODULAR MULTIFUNCTIONAL LED BEACONS

- Multifunctional LED beacon with high optical performance
- Compatible with 12-24VAC/DC or 120-240VAC (Voltage is dependent on selected base)
- Three separate inputs: steady, flashing and rotating
- 100000 hour LED
- Four mounting base options
- Type 4X, IP66
- CE compliant
- UL and cUL listed



Model No.	Mfg. No.	Description	Voltage	Price/Each
XE717	SLM100A	Amber	-	
XE718	SLM100B	Blue	-	
XE719	SLM100C	Clear	-	
XE720	SLM100G	Green	-	
XE721	SLM100R	Red	-	
<b>BASES</b>				
XE709	SLMBS-012-024GY	Shallow Mounting Base	12-24VDC/AC	
XE710	SLMBD-120-240GY	Deep Mounting Base	120-240VAC	

Note: Other mounting base options available.

## ELECTRARAY® HAZARDOUS LOCATION LED FLASHING WARNING LIGHTS WITH XLT™ TECHNOLOGY

- 120 VAC and 240 VAC
- Flashing mode standard (60 flash rate/minute), configurable to steady-burn
- 60000-hour, vibration-resistant LED lamp
- 1/2" pipe mount
- Type 4X, IP66 enclosure, marine listed
- UL and cUL listed for class 1, division 2 applications



Model No.	Mfg. No.	Colour	Price/Each
XC425	225XL-120-240A	Amber	
XC426	225XL-120-240B	Blue	
XC427	225XL-120-240R	Red	
XC428	225XL-120-240G	Green	

Note: Also available in 24 V AC/DC