## **CORDLESS POWER TOOLS & ACCESSORIES**

## 4 V M4<sup>TM</sup> 1/4" HEX SCREWDRIVERS

TLV691

- 21-position clutch setting with auto shut-off
- Includes: (2x) M4<sup>TM</sup> 2.0 battery and M4<sup>TM</sup> charger

#### **SPECIFICATIONS**

Voltage: 1/4" Hex Chuck Size: Maximum Torque: 44 in-lbs. # of Speed Settings: 2 # of Speed Settings: 2 No Load RPM Setting #1: 0-200 No Load RPM Setting #2: 0-600 **Clutch Settings:** 21 **Tool Weight:** 0.85 lbs.

Model No. TLV684 Mfg. No. 2101-22 Price/Each \$

Model No.:

Replacement Battery





# 12 V LITHIUM-ION SUB-COMPACT CORDLESS DRILL/DRIVER KITS

- Clutch settings: 14+1
- Features: Light compact design
- · Built-in LED light
- · Battery Fuel gauge
- Includes: (2x) 1.4 Ah Lithium-Ion Batteries, Charger and Tool bag
- Battery Type: Lithium-Ion

#### **SPECIFICATIONS**

Model No.:

 Voltage:
 12 V

 Chuck Size:
 1/4"

 Max Torque:
 150 in-lbs.

 # of Speed Settings:
 1

 No Load RPM Setting #1:
 0-500

 Chuck Type:
 Hex quick change

 Tool Weight:
 2.1 lbs.

 Replacement Battery

 Model No.
 Mfg. No.
 Desc.
 Price/Each

 TMB540
 2401-20
 Tool Only

 TLZ166
 2401-22
 Tool & Kit



Milwaukee

## 1/4" CORDLESS DRIVER/DRILL

- Auto stop system indicates battery power reduction and stops operation when battery reaches minimal capacity in order to prevent incomplete fastening
- Locking feature prevents accidental start up and enables use as a hand-held screwdriver
- Adjustable handle with enhanced hinge mechanism for operational versatility
- LED job light illuminates work area and features independent on/off switch
- Includes: Two 7.2 V Li-Ion (1.5 ah) batteries, charger, Phillips bit 1-50, Phillips bit 2-50, battery plastic case, plastic carrying case

### SPECIFICATIONS

Voltage: 7.2 V | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" |

Model No. TYW999 Mfg. No. DF012DSE Price/Each \$



Tankita

## XTREME™ BRUSHLESS SCREWDRIVER KIT

• Designed for hard to reach fastening applications that require clutch control

TLZ368

- · Brushless motor for Maximum runtime and durability
- · Quick release drop and load hex that accepts 1" bit tips
- 3 LED lights on nose for work surface illumination
- Includes: (1) 12 V Max\* brushless 1/4" screwdriver,
   (2) 12 V Max\* 2 Ah batteries with state of charge indicator,
   (1) 12 V and 20 V Max\* charger, (1) Belt clip, (1) Kit bag

#### **SPECIFICATIONS**

 Voltage:
 12 V

 Chuck Size:
 1/4"

 Max Torque:
 200 UWO

 No Load RPM Setting:
 0-1100

 Tool Weight:
 1.5 lbs.

Model No.	Mfg. No.	Desc.	Price/Each
UAF547	DCF601B	Tool Only	
UAF542	DCF601F2	Tool & Kit	





Milwaukee

### 8 V MAX\* GYROSCOPIC SCREWDRIVERS

**TNB487** 

- Good for fastening into wood, plastic and light-gauge metal
- Variable speed & reversing controls
- Adjustable 2-position handle allows for operation in either in-line or pistol-grip
- · Built-in LED light
- Includes: 8 V MAX\* compact battery, 1 hour charger and kit bag

#### **SPECIFICATIONS**

 Voltage:
 8 V

 Chuck Size:
 1/4" Hex

 No Load RPM:
 0-430

 Tool Weight:
 1.1 lbs.

 Replacement Battery

Model No. TLV653 Mfg. No. DCF680N1 Price/Each \$

Model No.:





# 12 V M12<sup>TM</sup> FUEL<sup>TM</sup> 1/4" HEX 2-SPEED SCREWDRIVERS

- Redlithium<sup>™</sup> Battery Technology delivers more work per charge and more work over pack life than any battery on the market
- Redlink Plus<sup>TM</sup> Intelligence provides optimized performance and overload protection using total system communication between tool, battery and charger
- LED light
- Includes: (2x) M12<sup>TM</sup> Redlithium<sup>TM</sup> 2.0 compact battery pack, M12<sup>TM</sup> Lithium-Ion battery charger, belt clip and hard carrying case

TLV694

#### **SPECIFICATIONS**

Model No.:

Voltage: 12 V Chuck Size: 1/4" Max Torque: 325 in-lbs. # of Speed Settings: No Load RPM Setting #1: 0-450 No Load RPM Setting #2: 0-1700 Chuck Type: Hex quick change **Tool Weight:** 2.0 lbs Replacement Battery

 Model No.
 Mfg. No.
 Desc.
 Price/Each

 TMB553
 2402-20
 Tool Only

 TLV679
 2402-22
 Tool & Kit



1104 TOOLS & EQUIPMENT