

# AIR TOOLS




## 5" NON-VACUUM DYNORBITAL-SPIRIT® RANDOM ORBITAL SANDERS

- Palm-style grip
- Colour-coded composite lever (identifies orbit size)
- Low sound levels
- One-piece speed control dial
- Custom engineered composite cylinder
- Double row balancer bearing keeps out contaminants
- Includes low profile, premium urethane, weight-mated, non-vac pad for use with PSA discs
- Can be converted easily to self-generated or central vac model for hook-up to dust collection system




TGY861



3/16" (5 mm) dia. orbit  
for general sanding




TGY852



3/8" (10 mm) dia. orbit  
for aggressive sanding



TGY870



3/32" (2.5 mm) dia. orbit  
for ultra-fine sanding



Model No	TGY861	TGY852	TGY870
<b>Mfg. No.</b>	59020	59005	59035
<b>Abrasive Information:</b>	5" dia. discs (127 mm)	5" dia. discs (127 mm)	5" dia. discs (127 mm)
<b>Pad Information:</b>	5" dia. pad (127 mm)	5" dia. pad (127 mm)	5" dia. pad (127 mm)
<b>Air Flow Rate @ 90 PSI:</b>	14 SCFM	14 SCFM	14 SCFM
<b>Sound Level:</b>	80 dB (A)	82 Db (A)	79 dB (A)
<b>Horsepower:</b>	0.25 HP	0.25 HP	0.25 HP
<b>Free Speed:</b>	12 000 RPM	12 000 RPM	12 000 RPM
<b>Air Pressure:</b>	90 PSI	90 PSI	90 PSI
<b>Air Inlet Thread:</b>	1/4 NPT	1/4 NPT	1/4 NPT
<b>Hose Size (I.D.):</b>	1/4" (6 mm)	1/4" (6 mm)	1/4" (6 mm)
<b>Orbit Diameter:</b>	3/16" (4.8 mm)	3/8" (9.5 mm)	3/32" (2.4 mm)
<b>Tool Spindle Thread:</b>	5/16"- 24 female	5/16"- 24 female	5/16"- 24 female
<b>Length:</b>	6 1/2" (165 mm)	6 1/2" (165 mm)	6 1/2" (165 mm)
<b>Height:</b>	3 1/2" (89 mm)	3 1/2" (89 mm)	3 1/2" (89 mm)
<b>Weight:</b>	1.4 lbs. (0.64 kg)	1.5 lbs. (0.68 kg)	1.4 lbs. (0.64 kg)
<b>Price/Each</b>	\$	\$	\$

## 6" NON-VACUUM DYNORBITAL-SPIRIT™ RANDOM ORBITAL SANDERS

- Palm-style grip
- Colour-coded composite lever (identifies orbit size)
- Low sound levels
- One-piece speed control dial
- Custom engineered composite cylinder
- Double row balancer bearing keeps out contaminants
- Includes low profile, premium urethane, weight-mated, non-vac pad
- Can be converted easily to self-generated or central vac model for hook-up to dust collection system



Model No.	TGY855	TGY873
<b>Mfg. No.</b>	59010	59040
<b>Abrasive Information:</b>	6" dia. discs (152 mm)	6" dia. discs (152 mm)
<b>Pad Information:</b>	6" dia. pad (152 mm)	6" dia. pad (152 mm)
<b>Air Flow Rate @ 90 PSI:</b>	14 SCFM	14 SCFM
<b>Sound Level:</b>	80 dB (A)	80 dB (A)
<b>Horsepower:</b>	0.25 HP	0.25 HP
<b>Free Speed:</b>	12 000 RPM	12 000 RPM
<b>Air Pressure:</b>	90 PSI	90 PSI
<b>Air Inlet Thread:</b>	1/4 NPT	1/4 NPT
<b>Hose Size (I.D.):</b>	1/4" (6 mm)	1/4" (6 mm)
<b>Orbit Diameter:</b>	3/8" (9.5 mm)	3/32" (2.4 mm)
<b>Tool Spindle Thread:</b>	5/16"- 24 female	5/16"- 24 female
<b>Length:</b>	7" (178 mm)	7" (178 mm)
<b>Height:</b>	3 1/2" (89 mm)	3 1/2" (89 mm)
<b>Weight:</b>	1.6 lbs. (0.73 kg)	1.5 lbs. (0.68 kg)
<b>Price/Each</b>	\$	\$

