

# FITTINGS, COUPLINGS & CLAMPS



## QUICK COUPLERS

High performance, corrosion resistant quick couplers built to interchange with industrial type couplings. Offer a higher flow for maximum on-line performance of hand-held air tools. Heavy-duty, high quality design.

**Industrial Plug  
TA249**



**Industrial Automax  
Automatic Coupler  
TZ184**



**Industrial Maxquik  
Manual Coupler  
TA268**



**Industrial Automax  
Automatic Coupler  
TZ228**



## TOPRING

### 1/4 INDUSTRIAL INTERCHANGE

#### 1/4 INDUSTRIAL PLUGS

- Zinc Plated or Stainless Steel 304
- Corrosion resistant

#### 1/4 INDUSTRIAL AUTOMAX COUPLERS

- Automatic push-to-connect operation
- Proven and positive connection using pin-lock mechanism
- Max 250 PSI
- 37 SCFM

#### 1/4 INDUSTRIAL MAXQUIK COUPLERS

- Manual operation
- Sleeve guard prevents accidental disconnection
- Max 250 PSI
- 24 SCFM

Size"	Model No.	Mfg. No.	Price/Each	Size"	Model No.	Mfg. No.	Price/Each	Size"	Model No.	Mfg. No.	Price/Each
<b>FEMALE THREAD (F) NPT</b>											
1/8	TA243	20.122	-	1/8	-	-	-	1/8	-	-	-
1/4	TA244	20.142	-	1/4	TZ184	20.444	-	1/4	TA268	20.842	-
1/4 (Stainless)	TLV344	20.146	-	1/4 (Stainless)	-	-	-	1/4 (Stainless)	-	-	-
3/8	TA245	20.162	-	3/8	-	-	-	3/8	TA269	20.862	-
<b>MALE THREAD (M) NPT</b>											
1/8	TA247	20.222	-	1/8	-	-	-	1/8	-	-	-
1/4	TA248	20.242	-	1/4	TZ185	20.644	-	1/4	TA271	20.942	-
1/4 (w/thread sealant)	TLV345	20.248	-	1/4 (w/thread sealant)	-	-	-	1/4 (w/thread sealant)	-	-	-
1/4 (Stainless)	TLV346	20.246	-	1/4 (Stainless)	-	-	-	1/4 (Stainless)	TLV348	20.946	-
3/8	TA249	20.262	-	3/8	TZ227	20.664	-	3/8	TA272	20.962	-
<b>HOSE BARB</b>											
1/4 I.D.	TA252	20.342	-	1/4 I.D.	TZ228	20.744	-	1/4 I.D.	TA258	20.542	-
5/16 I.D.	TA253	20.352	-	5/16 I.D.	-	-	-	5/16 I.D.	-	-	-
3/8 I.D.	TA254	20.362	-	3/8 I.D.	TZ230	20.764	-	3/8 I.D.	TA260	20.562	-

### 3/8 INDUSTRIAL INTERCHANGE

#### 3/8 INDUSTRIAL PLUGS

- Zinc plated steel construction
- Corrosion resistant

#### 3/8 INDUSTRIAL AUTOMAX COUPLERS

- Automatic push-to-connect operation
- Proven and positive connection using pin-lock mechanism
- Max 250 PSI
- 62 SCFM

#### 3/8 INDUSTRIAL MAXQUIK COUPLERS

- Manual operation
- Sleeve guard prevents accidental disconnection
- Max 250 PSI
- 56 SCFM

Size"	Model No.	Mfg. No.	Price/Each	Size"	Model No.	Mfg. No.	Price/Each	Size"	Model No.	Mfg. No.	Price/Each
<b>FEMALE THREAD (F) NPT</b>											
1/4	TA273	21.142	-	1/4	TA281	21.442	-	1/4	TZ144	21.842	-
3/8	TA274	21.162	-	3/8	TA282	21.462	-	3/8	TZ145	21.862	-
1/2	TZ132	21.182	-	1/2	TZ137	21.482	-	1/2	TZ146	21.882	-
<b>MALE THREAD (M) NPT</b>											
1/4	TA278	21.242	-	1/4	TZ138	21.642	-	1/4	TZ147	21.942	-
3/8	TA279	21.262	-	3/8	TA283	21.662	-	3/8	TZ148	21.962	-
1/2	TZ133	21.282	-	1/2	TZ139	21.682	-	1/2	TZ149	21.982	-
<b>HOSE BARB</b>											
3/8 I.D.	TA280	21.362	-	3/8 I.D.	TZ142	21.762	-	3/8 I.D.	TZ152	21.562	-
1/2 I.D.	TZ136	21.382	-	-	-	-	-	1/2 I.D.	TZ153	21.582	-

### 1/2 INDUSTRIAL INTERCHANGE

#### 1/2 INDUSTRIAL PLUGS

- Zinc plated steel construction
- Corrosion resistant

#### 1/2 INDUSTRIAL AUTOMAX COUPLERS

- Automatic push-to-connect operation
- Proven and positive connection using pin-lock mechanism
- Max 250 PSI
- 99 SCFM

#### 3/8 INDUSTRIAL MAXQUIK COUPLERS

- Manual operation
- Sleeve guard prevents accidental disconnection
- Max 250 PSI
- 75 SCFM

Size"	Model No.	Mfg. No.	Price/Each	Size"	Model No.	Mfg. No.	Price/Each	Size"	Model No.	Mfg. No.	Price/Each
<b>FEMALE THREAD (F) NPT</b>											
3/8	TZ154	22.162	-	3/8	-	-	-	3/8	-	-	-
1/2	TZ155	22.182	-	1/2	TZ165	22.482	-	1/2	TZ175	22.882	-
3/4	TZ156	22.192	-	3/4	-	-	-	3/4	TZ176	22.892	-
<b>MALE THREAD (M) NPT</b>											
3/8	TZ158	22.262	-	3/8	-	-	-	3/8	-	-	-
1/2	TZ159	22.282	-	1/2	TZ169	22.682	-	1/2	TZ179	22.982	-
3/4	TZ160	22.292	-	3/4	-	-	-	3/4	TZ180	22.992	-
<b>HOSE BARB</b>											
3/8 I.D.	TZ161	22.362	-	3/8 I.D.	-	-	-	3/8 I.D.	-	-	-
1/2 I.D.	TZ162	22.382	-	-	-	-	-	1/2 I.D.	TZ182	22.582	-