

## PIPEFITTER™ GRINDING WHEEL

- Outstanding performer in pipeline construction
- These wheels are specially formulated and reinforced for grinding joint welds between passes in pipeline construction and pipe fabrication
- They do not contain iron, sulfur or chlorine (Fe, S, Cl) and will not contaminate stainless steel
- **3/32" Thick:** Thin for fast and free cutting and grooving; can also be used for cutting sheet metal
- **5/32" Thick:** Formulated for light grinding, cutting and notching
- **1/8" Thick:** Ideal for use with low power angle grinders; grind joint welds with ease; can be used for intermittent light grinding, facing and bevelling work



Model No.	Mfg. No.	Size			Grade	Max RPM	Price /Each
		D"	x	A"			
VV103	08-N-453	4 1/2	x 3/32	x 7/8	A-36-PIPE	13 300	
VV104	08-N-503	5	x 3/32	x 7/8	A-36-PIPE	12 200	
VV380	08-N-603	6	x 3/32	x 7/8	A-36-PIPE	10 200	
VV106	08-N-703	7	x 3/32	x 7/8	A-36-PIPE	8 600	
VV385	08-N-454	4 1/2	x 5/32	x 7/8	A-36-PIPE	13 300	
VV386	08-N-504	5	x 5/32	x 7/8	A-36-PIPE	12 200	
VV105	08-N-604	6	x 5/32	x 7/8	A-20-PIPE	10 200	
VV107	08-N-704	7	x 5/32	x 7/8	A-20-PIPE	8 600	
VV381	08-N-452	4 1/2	x 1/8	x 7/8	A-36-PIPE	13 300	
VV382	08-N-502	5	x 1/8	x 7/8	A-36-PIPE	12 200	
VV383	08-N-602	6	x 1/8	x 7/8	A-36-PIPE	10 200	
VV384	08-N-702	7	x 1/8	x 7/8	A-36-PIPE	8 600	

## FLEXCUT™ TYPE 27

- Premium performance flexible grinding wheel especially formulated to deliver superior performance on all ferrous and non-ferrous metals
- Deep Diamond-Cut™ pattern and optimized formulation
- More flexibility
- Best handling on flat and curved surfaces
- Cooler grinding
- Better stock removal in all materials (steel, stainless steel, aluminum)
- 4 1/2" and 5" Flexcut™ flexible grinding wheels with the unique Spin-on quick change mounting system for better comfort and maximum productivity
- Always use flange model UG580



Model No.	Mfg. No.	Size			Grade	Max RPM	Price /Each
		D"	x	A"			
VV411	15-L-453	4 1/2	x 5/8"-11		A-36-X-FLEX	13 300	
VV412	15-L-456	4 1/2	x 5/8"-11		A-60-X-FLEX	13 300	
VV413	15-L-460	4 1/2	x 5/8"-11		A-100-X-FLEX	13 300	
VV414	15-L-503	5	x 5/8"-11		A-36-X-FLEX	12 200	
VV415	15-L-506	5	x 5/8"-11		A-60-X-FLEX	12 200	
VV416	15-L-510	5	x 5/8"-11		A-100-X-FLEX	12 200	
UG128	15-L-602	6	x 5/8"-11		A-24-X-FLEX	10 200	
UG129	15-L-603	6	x 5/8"-11		A-36-X-FLEX	10 200	
UG130	15-L-606	6	x 5/8"-11		A-60-X-FLEX	10 200	
VV139	15-L-702	7	x 7/8"		A-24-X-FLEX	8 600	
VV140	15-L-703	7	x 7/8"		A-36-X-FLEX	8 600	
VV141	15-L-706	7	x 7/8"		A-60-X-FLEX	8 600	
VV142	15-L-710	7	x 7/8"		A-100-X-FLEX	8 600	

D x T x A: Diameter x Thickness x Arbor Size  
D x A: Diameter x Arbor Size

## ANGLE GRINDERS WITH TRIGGER GRIP

- Trigger grip handle provides better control, reach and leverage
  - Debris baffles protect internal components by deflecting damaging debris out of the airflow at the intake vents
  - External brush doors reduces service time by providing easy access to brushes
  - Includes: Side handle, spanner wrench and type 27 guard
  - Wheel Diameter: 5"
  - Voltage: 120 V
  - Amps: 11 A
  - No Load RPM: 11 000
  - Spindle Size: 5/8"
  - Tool Weight: 5.6 lbs.
- Model No. TLZ810**  
**Mfg. No. 6121-31A**  
**Price/Each \$**



## HEAVY-DUTY ANGLE GRINDERS

- High power-to-weight ratio for greater efficiency and reduced user fatigue
  - External brush doors for easy servicing
  - Sealed ball and roller bearings for extended motor life
  - Includes: Grinding wheel, wrench, keyless adjustable guard and two position side handle
  - Wheel Diameter: 5"
  - Voltage: 120 V
  - Amps: 12 A
  - No Load RPM: 10 000
  - Spindle Size: 5/8"
  - Tool Weight: 7.4 lbs.
- Model No. VE980**  
**Mfg. No. DW831**  
**Price/Each \$**



## ANGLE GRINDERS

- Rear handle design for greater control
  - Trigger lock
  - Light weight for high production work with less fatigue
  - Includes: 5" grinding wheel 24 grit and side handle
- Model No. TF719**  
**Mfg. No. 9005B**  
**Price/Each \$**

### SPECIFICATIONS

**Wheel Diameter:** 5"  
**Voltage:** 120 V  
**Amperage:** 10 Amp  
**No Load RPM:** 10 000  
**Spindle Size:** 5/8"  
**Tool Weight:** 6.6 lbs.

